

Unify-Produktvergleich mobile Endgeräte

Mobile/DECT	OpenScape DECT/WLAN Phone					
	S6	S6 Base (analog)	SL6	R6	WL4 Plus	M3 Plus Ex
						

Display

Beleuchtetes Display (Pixel)	240 x 320				128 x 160	
------------------------------	-----------	--	--	--	-----------	--

Leistungsmerkmale

Ex-Zulassung (Kennzeichen: II2GEEEx ib IIC T4)	—				M3 Ex	
Personen-Notsignal	—				WL4 plus	M3 plus
Gehäuse-Schutzart	—		IP65		—	IP65
Tastaturbeleuchtung	ja					
Freisprechtaste	ja					
Tasten individuell programmierbar	ja					
Telefonbucheinträge	ca. 500				max. 250	ca. 500
Vibrationsalarm	ja					
Headsetanschluß	3,5 mm Klinke oder Bluetooth V2.1				3,5 mm Klinke	2,5 mm Klinke oder Bluetooth V2.1
PC- Interface	Micro-USB oder Bluetooth				—	Mini-USB oder Bluetooth
Stromversorgung	2x NiMH AAA		Lithium-Ionen-Akku	2x NiMH AAA		Lithium-Ionen-Akku
Abmessungen (H x B x T) in mm	159 x 53 x 24		130 x 51 x 19	159 x 55 x 25		137 x 52 x 21 154 x 56 x 26